

KIRLIN MASTER OPTION LIST

- 10 Tinted lens instead
- 11 Tempered prismatic Kirlin lens
- 12 Prismatic acrylic overlay with 1/4" polycarbonate below
- 13 Clear flat polycarbonate below with prismatic flat lens above
- 14 Dropped opal glass
- 15 Prismatic flat glass lens
- 17 Prismatic high strength acrylic lens
- 18 Opal flat glass
- 20 White ½ cube eggcrate aluminum louver
- 21 White translucent flat polycarbonate diffuser
- 23 Frosted microprismatic lens instead
- 25 Vandal/ligature resistant trim, hardware and lensing
- 26 Tamper resistant button head screw with center pin; 1 key/10 fixtures
- 27 Vandal resistant lens above ¼" clear tempered glass
- 28 UV absorbing clear tempered glass
- 29 Two wire (Lutron) LED PWM dimming
- 30F White enamel (flange only)
- 30T White enamel (complete trim)
- 31 White enamel (flange only)
- 32 White trim extender, specify OD
- 33 Tempered glass Glow Ring suspended beneath trim; shape matches reflector
- 34 On-Off switch
- 35 Silver enamel finish
- 35F Silver enamel (flange only)
- 35T Silver enamel (complete trim)
- 36 Gold enamel finish
- 37 Dark bronze enamel finish
- 37F Dark bronze enamel (flange only)
- 37T Dark bronze enamel (complete trim)
- 38 Black enamel finish
- 38F Black enamel (flange only)
- 38T Black enamel (complete trim)
- 40 White grooveless flare trim
- 41 Drop asymmetric prismatic polycarbonate lens
- 42 Drop polycarbonate bisymmetric prismatic lens
- 44 Black OptiGroove regressed trim
- 45 Gasket between trim and ceiling
- 46 Gasket between lens and trim
- 47 Wet plaster frame for wet plaster ceiling
- 50 Gray wallplate instead
- 51 Ivory wallplate instead
- 54 Safety cable through pendant stem
- 55 Custom length safety cable through pendant stem
- 58 277 volt: 60 Hz. Ballast; 277V line input; or 277/120V stepdown transformer
- 62T Clear specular finish (complete trim)
- 70T Clear semi-specular SofTex™ (complete trim)
- 76 Drop white polycarbonate lens instead
- 78 Concrete pour box assembly
- 79 Extension collar for ceilings up to 2" thick
- 80 2" collar for mounting beneath surface outlet box; covered ceilings only
- 81 15° bottom pan (motorized medical)
- 82 Sloped ceiling adapter for slopes up to 30° in 5° increments
- 84 Fixture wired for two circuits instead of one
- 85 Ceiling Panel; lays-in 2'x 2' grid
- 86 Lensed WeatherCap™ for indirect position of direct/indirect Wet Label fixtures
- 87 Custom pendant/wall bracket length (Motorized: Cable length greater than 35 ft)
- 88 Swivel canopy, for sloped ceilings up to 40°
- 89 Sealed top WeatherCap™ for Wet Label wall bracket or pendant mounts
- 94 Custom color/finish
- 97 Other voltage ballast
- 98 347 volt 50 Hz. ballast instead
- 99 Special modification
- 27K LED color temperature 2700°K instead
- 30K LED color temperature 3000°K instead
- 40K LED color temperature 4000°K instead (XICATO®)
- 41K LED color temperature 4100°K instead
- 50K LED color temperature 5000°K instead
- 120 Power supply (and thermal protector) rated for 120V
- 277 Power supply (and thermal protector) rated for 277V
- AC Aircraft cable pendant mount with coiled cord
- ADA ADA compliant
- AM Amber filter
- AS Aircraft cable pendant mount with straight cord
- ASB Aircraft cable pendant mount; black straight cord
- ASW Aircraft cable pendant mount; white straight cord
- AT Air Tight version; Meets ASTM E283 airflow restriction of 2CFM max
- BG Kirlin BioGard™ anti-microbial finish (white only)
- BGT Kirlin BioGard™ anti-microbial finish trim (white only)
- BI Beeper inactivated (INFRALED® series remote control)
- BL Blue LED filter instead
- BLF Black finial finish
- BN Brushed satin nickel finish
- BRF Brass finial finish
- CC Clear tempered glass lens at ceiling
- CF Custom color filter (Rosco); specify
- CL Custom image (color/logo) in sconce center field
- CMB Cord pendant mount, black instead
- COF Cone shaped finials
- CS Prismatic tempered lens at ceiling
- CUF Custom color finial finish
- CV Convex opal polycarbonate lens instead
- D1 0-10V 1.0% dimming instead
- D2 0-10V 0.1% dimming instead
- D3 DALI 1.0% dimming instead
- D4 DALI 100-0.1% dimming instead
- D5 DMX512A 0% dimming instead
- D6 Triac incandescent 100-10% dimming instead; 120V only
- D7 DALI dual drive 0.1% dimming driver instead
- D8 DALI DT8 dual drive 0.1% dimming driver instead
- DAL For use with DALI system controls; Consult factory
- DF Electrically isolated "dead front" gasketed trim (LED)
- DG Drop Guard with prismatic flat glass
- DL Downlight version instead
- DM Dimmer installed in fixture J-box (samples only)
- DMX For use with DMX512A-RDM controls; dim to black
- DN Downlight only version of direct/indirect luminaire
- DW Double wall wash; 180° opposite
- ECO For use with Lutron EcoSystem controls; dim to black; consult factory
- EI Remote emergency inverter: For 100% rated lumens up to -3000L; 90+ minutes; N/A for options -29 or -FS
- EI4 Remote emergency inverter: For 100% rated lumens up to -4000L; 90+ minutes; CEC Compliant; N/A for options -29 or -FS
- EI5 Remote emergency inverter: For 100% rated lumens up to -5000L; 90+ minutes; N/A for options -29 or -FS
- EM Internal emergency battery pack; 90+ minutes; **see product submittal sheets for rated lumen output**

KIRLIN MASTER OPTION LIST

- ERH Remote emergency battery pack; delivers 1000 lumens; 90+ minutes
- FC Frosted prismatic tempered lens at ceiling
- FD Double Fused primary; Use with -84; Aids servicing
- FF Fastener Free faceplate/trim
- FP Frosted prismatic tempered lens
- FR Fresnel tempered lens; Concentric prisms
- FRS Frosted K lens instead
- FS Fused primary; One per fixture
- FT Flat white trim instead
- G1 Hospital grade duplex GFCI installed on one side
- G2 Hospital grade duplex GFCI installed on both sides
- GE Green/Botanical filter
- GF Hospital grade GFCI (ground fault circuit interrupt) duplex receptacle; grounded
- GL Green acrylic lens
- H1 Hospital grade duplex receptacle installed on one side
- H2 Hospital grade duplex receptacle installed on both sides
- HC 90+ CRI instead; 30K only; Consult factory for availability
- HD Hospital grade grounded convenience receptacle
- HW Higher wattage LED; Increases lumen output 30%.
- HX Hexcel (low voltage) louver
- I65 IP65 rated trim and lens
- I66 IP66 rated trim and lens
- L1 .140" high strength acrylic prismatic lens instead; one side
- L2 .140" high strength acrylic prismatic lens instead; both sides
- LL UV absorbing tempered linear lens; Lengthwise distribution is four times width
- LP With lamp(s); Specify source, wattage, color temperature and clear or coated, if applicable
- LWC For use with LeGrand Wattstopper controls; Dim to black
- MB Medium Blue filter
- MC Microprismatic clear tempered lens at ceiling
- MFL Medium flood distribution
- MR Converted to non-ferrous construction for MRI use
- NAT Modified for natatorium use
- NC Non-conductive spring clip sleeves
- NFL Narrow flood distribution instead
- NS NSF approved fixture; Not available with Option -25
- OG OptiGroove; black seamless tapered aluminum. White trim, self-flanged
- OR Orange LED filter instead
- PC Photocell; Illuminates NightLight when room is dark
- PC1 Photocell, one side; Illuminates NightLight when room is dark
- PC2 Photocell, both sides. Illuminates NightLight when room is dark
- PM Pendant mount instead
- PSQ Lutron T-Series controls instead
- QM QuickConnect mount for surface cylinders
- RA Red/Amber LED filter instead
- RC Extra remote control (motorized medical systems)
- RE Red LED filter instead
- RH Residential mounting hardware instead
- ROF Round shaped finials
- RS Remote sensor; Consult factory (motorized medical)
- S1 Hospital grade push button on-off switch installed on one side; Controls both lamps
- SE Seismic anchorage provided; (motorized medical)
- SG Shatter Guard; 1/8" clear polycarbonate below lamps
- SH Sealed housing and J-box
- SM Surface mount instead

- SN Super narrow housing instead
- SP Shallow plenum version
- SPT Spot distribution instead
- SQ Square trim instead
- SS Remote mounted Kirlin SmartSupply™ LED driver instead, sold separately
- TA Top Access for servicing from above ceiling
- WA White acrylic (flat) diffuser instead
- WB Wall-bracket mount instead
- WFL Wide flood distribution instead
- WHF White finial finish
- WL NightLight UL Wet Location listed
- WW Wall wash assembly instead
- YE Yellow LED filter instead